



 $\begin{array}{lll} \text{Composition} & \text{Di-tertiary amyl hydroquinone} \\ \text{CAS No.} & 79\text{-}74\text{-}3 \\ \text{EC No.} & 201\text{-}222\text{-}2 \\ \text{Molecular Formula} & C_{14}H_{20}O_2 \\ \text{Molecular Weight} & 250 \\ \end{array}$

Property	Unit	Typical Value	Test Method
Appearance	J- II	White to off white powder	Visual
Assay	%	95.0 min.	QCD/TM/72
Odour	1 - 1	Characteristic	QCD/TM/28
Melting Point	°C	177.0 -184.0	QCD/TM/25
Volatiles	%	0.50 max.	QCD/TM/24
Ash Content	%	0.10 max.	QCD/TM/11

Application:

- YAPOX®2275 is a phenolic Primary antioxidant /stabilizer based on sterically hindered dihydroxybenzene.
- It is a nonstaining & non discolourising antioxidant cum stabilizer for organic polymer
- Exhibit excellent protection against oxygen & sun crack
- Good scorch resistance
- Excellent Anti-skinning property.

USES -

- Unvulcanised rubber adhesive, tapes & films
- Cable & Wires
- Stabilization of Polymers & elastomers
- Hotmelt Adhesives
- Paints.

Packing:

Available in 25 Kg. Fibre Drum.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT. 01.06.2020

YAPOX is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail:info@yashoindustries.com

FACTORY - UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447