



Technical Data Sheet

YAPOX® AR 6768

Composition	N,N-bis(2-Ethylhexyl)-ar-methyl-1H-benzotriazole-1 methanamine
EC No.	939-700-4

Property	Unit	Typical Value	Test Method
Appearance	-	Clear, yellow to brown liquid	Visual
Density (@ 25°C)	gm/ml	0.94 - 0.96	ASTM D 1481
Color	-	L 1.5	ASTM D 1500
Viscosity (@ 40°C)	cSt	20.0 -90.0	ASTM D 0445
Viscosity (@ 100°C)	cSt	4.0 - 6.0	ASTM D 0445
Flash Point, PMCC	°C	125.0	ASTM D 92 - 02b

Application:

YAPOX®AR 6768 acts as corrosion inhibitor in printing inks/lube.

Packing:

Available in 200 Kg. Drum.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT.01.06.2020

YAPOX is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai - 400058, India
TEL.: +91 22 62510100/FAX: +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY - UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

www.yashoindustries.com