



# Technical Data Sheet

## YAPOX®BHT

### (BUTYLATED HYDROXY TOLUENE)

Composition	White to yellow crystals/flakes
CAS No.	128-37-0
EC No.	204-881-4
Molecular Formula	C <sub>15</sub> H <sub>24</sub> O
Molecular Weight	220

Property	Unit	Typical Value	Test Method
Appearance	-	White to off white Granular Powder	Visual
Assay	%	99.0 Min.	QCD/TM/72
Melting point	°C	69.0 - 70.0	QCD/TM/25
Moisture content	%	0.50 max.	QCD/TM/26
Ash content	%	1.0 max.	QCD/TM/11

#### Application:

YAPOX®BHT is used as an Antioxidants for Edible Oils, Lube, Plastic and Resins.

#### Packing:

Available in 25 Kg. Paper Bag

#### Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

#### Safety:

Please refer safety data sheet.

Rev.03 DT. 01.05.2020

YAPOX is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

#### **YASHO INDUSTRIES LIMITED**

**REGISTERED OFFICE:** Office No. 101/102, Peninsula Heights, C.D Barfiwala Marg, Juhu lane, Andheri (West), Mumbai - 400058, India. TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: [info@yashoindustries.com](mailto:info@yashoindustries.com)

**FACTORY - UNIT I:** Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.