

Technical Data Sheet

YAPOX®BZT

 $\begin{array}{lll} \text{Composition} & \text{Benzotriazole} \\ \text{CAS No.} & 95\text{-}14\text{-}7 \\ \text{EC No.} & 202\text{-}394\text{-}1 \\ \text{Molecular Formula} & C_6H_5N_3 \\ \text{Molecular Weight} & 119 \\ \end{array}$

Property	Unit	Typical Value	Test Method
Appearance	-	Off white crystalline powder	Visual
Assay (Titration)	%	98.0 min.	QCD/TM/43
Melting Point	°C	95.0 – 98.0	QCD/TM/25
Moisture Content (by KF)	%	0.25 max.	QCD/TM/26
Ash Content	%	0.25 max.	QCD/TM/11

Application:

YAPOX®BZT acts as a Corrosion Inhibitor for Lubricants, Petroleum Fuels, Hydraulic Fluids, Cutting Oils, Engine Coolants, Paints & Ink, Copper Processing, Plating Bath, Heating & Cooling System, Industrial Water Cooling and for Water Treatment Chemicals.

Packing:

Available in 20 Kg. HDPE Bag.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT. 01.06.2020

YAPOX is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: info@yashoindustries.com
FACTORY - UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL:: +91 260 2432421 / 2426894 /

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

www.yashoindustries.com