# **Technical Data Sheet**

# YAPOX®LM 30/10



CompositionHydroquinone bis(2-hydroxyethyl) etherCAS No.104-38-1EC No.203-197-3Molecular FormulaC10H14O4Molecular Weight198

Unit	<b>Typical Value</b>	Test Method
-	Grayish white powder/pellets	Visual
%	90.0 min.	QCD/TM/74
%	99.0 min.	QCD/TM/74
%	0.1 max.	QCD/TM/26
°C	98.0 min.	ASTM D 1519
Sec.	$100.0 \pm 20.0$	QCD/TM/109
mg KOH/gm	$560.0 \pm 20.0$	QCD/TM/22
	- % % °C Sec.	- Grayish white powder/pellets   % 90.0 min.   % 99.0 min.   % 0.1 max.   °C 98.0 min.   Sec. 100.0 ± 20.0

### **Application:**

YAPOX<sup>®</sup>LM 30/10 is used as Crosslinking agent / as a chain extender for polyurethanes (PU).

#### Packing:

Available in 125 Kg. Drum.

#### **Storage stability:**

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

## Safety:

Please refer safety data sheet.

Rev.03 DT.01.06.2020

YAPOX is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

#### YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL : +91 22 62510100/FAX : +91 22 62510199 E-Mail.:info@yashoindustries.com FACTORY – UNIT II: Plot No. 1713, Phase III, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2420896 / 2423896

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.