

# **Technical Data Sheet**

# **YAPOX®TTZ**

Composition Tolyltriazole
CAS No. 29385-43-1
EC No. 249-596-6
Molecular Formula C<sub>7</sub>H<sub>7</sub>N<sub>3</sub>
Molecular Weight 133

Property	Unit	Typical Value	<b>Test Method</b>
Appearance	-/	Pale yellow granular/powder	Visual
Assay	%	99.0 min.	QCD/TM/69
Melting Point	°C	82.0 -89.0	QCD/TM/25
Water Content	%	0.25 max.	QCD/TM/26
Ash Content	%	0.25 max.	QCD/TM/11

## Application:

YAPOX®TTZ acts as Corrosion Inhibitor for Lubricants, Petroleum Fuels, Hydraulic Fluids, Cutting Oils, Engine Coolants, Paints & Ink, Copper Processing, Plating Bath, Heating & Cooling System, Industrial Water Cooling and for Water Treatment Chemicals.

# Packing:

Available in 25 Kg. Bag.

#### **Storage stability:**

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

### Safety:

Please refer safety data sheet.

Rev.03 DT.01.06.2020

YAPOX is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

#### YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai - 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: <a href="mailto:info@yashoindustries.com">info@yashoindustries.com</a>
FACTORY - UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447