



Technical Data Sheet

YALUB®525 S

Composition Molybdenum Dithiocarbamate

Property	Unit	Typical Value	Test Method
Appearance	-	Dark Brown liquid	Visually
Molybdenum Content	%	10.0 – 11.0	ASTM D 7303
Sulfur Content	%	10.5 – 12.5	ASTM D 4239
Density (@ 15°C)	gm/cm ³	1.0400 – 1.0800	ASTM D 1481
Viscosity (@ 40°C)	mm ² /s	600.0 – 800.0	ASTM D 0445
Flash Point	°C	135.0 min.	ASTM D 93

Application:

YALUB®525 S is used as friction reducer in diesel engine oil, gasoline engine oil, gear oil, metal working fluid, grease.

Packing:

Available in 200 Kg Drum.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT. 01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY – UNIT II: Plot No. 1713, Phase III, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2420896 / 2423896

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.