



Technical Data Sheet

YALUB®822 M

Composition Molybdenum Dialkyldithiocarbamate

Property	Unit	Typical Value	Test Method
Appearance	-	Brown liquid	Visually
Molybdenum Content	%	4.5 – 5.3	ASTM D 7303
Sulphur Content	%	5.0 – 7.0	ASTM D 4239
Nitrogen Content	%	1.0 – 2.0	ASTM D 4629
Viscosity (@100°C)	cSt	12.0 – 17.0	ASTM D 0445
Density (@15.6°C)	gm/ml	0.98	ASTM D 1481
Solubility	-	Soluble in petroleum products. Insoluble in water.	QCD/TM/81

Application:

YALUB®822 M is a friction reducer and antioxidant for petroleum products. It may also maintain or improve the anti-friction properties of engine oil while reducing the phosphorous content.

Packing:

Available in 200 Kg Drum.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT. 01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY – UNIT II: Plot No. 1713, Phase III, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2420896 / 2423896

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.