



Technical Data Sheet

YALUB®85 M

Composition

Organomolybdenum complex of organic amide

Property	Unit	Typical Value	Test Method
Appearance	-	Brown liquid	Visually
Color 1% in oil	-	5.0 Max.	ASTM D 1500
Molybdenum Content	%	7.3 – 8.5	ASTM D 7303
Nitrogen Content	%	2.3 – 3.3	ASTM D 4629
Viscosity (@ 100°C)	cSt	60.0 – 100.0	ASTM D 0445
Density (@ 20°C)	mg/m ³	1.05 – 1.10	ASTM D 1481
Solubility	-	Soluble in petroleum products. Insoluble in water.	QCD/TM/81

Application:

YALUB®85M used as a molybdenum ester/amide friction modifier and antioxidant in engine oils.

Packing:

Available in 200 kgs Drum.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT. 01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY – UNIT II: Plot No. 1713, Phase III, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2420896 / 2423896

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

www.yashoindustries.com