# **Technical Data Sheet**





CAS No. 36878-20-3 EC No. 253-249-4 Molecular Formula  $C_{30}H_{47}N$  Molecular Weight 422

Property	Unit	Typical Value	<b>Test Method</b>
Appearance	- /	Dark Brown viscous liquid	Visual
Density (@ 25°C)	g/cm³	0.930 - 0.970	ASTM D 1481
Viscosity (@ 40°C)	cSt	500 – 900	ASTM D 0445
Flash Point	°C	> 100	ASTM D 92 <b>-</b> 02b
Nitrogen Content	%	3.2 – 3.8	ASTM D 5291 - 10
Chlorine Content	ppm	200 Max.	QCD/TM/90
Moisture Content	%	0.50 Max.	ASTM D 4377
Solubility		Soluble in Petroleum and Synthetic	QCD/TM/81
		Lubricant bases, Insoluble in water.	

### Application:

YALUB®DND is used as an antioxidant in mineral & synthetic oils. Its liquid form allows easy handling & blending.

## Packing:

Available in 25/200 Kg. Drum.

### Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

#### Safety:

Please refer safety data sheet.

Rev.03 DT. 01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

#### YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY - UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.