



Technical Data Sheet

YALUB®LA

Composition bis[O,O-bis(2-ethylhexyl) dithiophosphorato-S,S']dioxodi-μthioxodimolybdenum
EC No. 947-946-9

Property	Unit	Typical Value	Test Method
Appearance	-	Dark Green Liquid	Visually
Molybdenum Content	%	7.70 – 8.80	QCD/TM/133
Sulfur Content	%	11.0 – 13.8	ASTM D 1552
Density (@ 15.6°C)	gm/ ml	1.075 – 1.085	ASTM D 2320
Phosphorous Content	%	5.5 – 7.0	ASTM D 1091
Viscosity (@ 100°C)	cSt	6.0– 10.0	ASTM D 445
Solubility	-	Soluble in petroleum oils and greases, aliphatic & aromatic solvents and in various synthetic lubricants bases. Insoluble in water.	QCD/TM/81

Application:

YALUB®LA is used as friction modifier for lubricants.

Packing:

Available in 200 kgs Drum.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT.01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY – UNIT II: Plot No. 1713, Phase III, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2420896 / 2423896

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.