



Technical Data Sheet

YALUB[®]NA-A

Composition

Alkylated Phenyl Alpha Naphthylamine

Property	Unit	Typical Value	Test Method
Appearance	-	Brown liquid	Visually
Refractive Index (@ 25°C)	-	1.5500 - 1.6500	QCD/TM/76
Density (@ 20°C)	gm/cm ³	0.9900-1.0100	QCD/TM/77
Flash Point	°C	220 - 290	ASTM D 92 - 02b

Application:

YALUB[®]NA-A is a powerful, low - sludging antioxidant which provides excellent stability in petroleum products. It is an especially cost effective liquid antioxidant used in applications such as Turbine oils, Compressor oils, Quenching and Hydraulic oils. It is a high performance antioxidant which has excellent free radical scavenging abilities in a wide variety of base stocks including mineral, hydro-treated, synthetic and vegetable oils.

Packing:

Available in 200 Kg. Drum.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT. 01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai - 400058, India TEL: +91 22 62510100/FAX : +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY - UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

www.yashoindustries.com