



Technical Data Sheet

YALUB®NATD

Composition Disodium 2,5-dimercapto-1,3,4-thiadiazole,
30% aqueous solution

Property	Unit	Typical Value	Test Method
Appearance	-	Pale yellow to Amber color liquid	Visually
Solid Content	%	30.0 min.	QCD/TM/256
Specific Gravity (@ 25°C)	-	1.20 – 1.24	QCD/TM/77
pH (@RT)	-	8.5 – 10.5	QCD/TM/31

Application:

YALUB®NATD is a corrosion inhibitor and metal deactivator for nonferrous metals in aqueous systems.

Packing:

Available in 50/230 Kg HDPE Drum.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT.01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX: +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY – UNIT II: Plot No. 1713, Phase III, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2420896 / 2423896

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.