



Technical Data Sheet

YALUB®PA 15 S

Composition	Thiodiethylene bis[3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate]
CAS No.	41484-35-9
EC No.	255-392-8
Molecular Formula	C ₃₈ H ₅₈ O ₆ S
Molecular Weight	643

Property	Unit	Typical Value	Test Method
Appearance	-	Crystalline white to yellow powder	Visually
Melting point	°C	63.0 - 74.0 min.	ASTM D 1519
Moisture content	%	3.0 max.	ASTM E 1868
Ash content	%	0.1 max.	ASTM D 0874
Sulfur content	%	4.0 - 6.0	ASTM D 4951

Application:

YALUB®PA 15 S is high molecular phenolic antioxidant used in hydraulic fluids, metalworking fluids, industrial gear oils, turbine oils, polyglycols, and use with natural and synthetic esters.

Packing:

Available in 25 Kg. Paper Bag.

Storage stability:

Store in a cool and dry place. Stable for up to 24 months from the date of manufacturing when stored in the original packing material in a cool and dry environment.

Safety:

Please refer safety data sheet.

Rev.03 DT. 01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai - 400058, India TEL: +91 22 62510100/FAX : +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY - UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.
www.yashoindustries.com