

Technical Data Sheet

YALUB®TT 33

Composition Tolytriazole derivatives
 EC No. 939-700-4

Property	Unit	Typical Value	Test Method
Appearance	-	Clear yellowish to brown liquid	Visually
Density (@ 25°C)	-	0.94 – 0.96	QCD/TM/77
Color	-	L 1.5	ASTM D 1500
Viscosity (@ 40°C)	cSt	20.0 – 90.0	QCD/TM/208
Viscosity (@ 100°C)	cSt	4.0 – 6.0	QCD/TM/208
Flash Point, PMCC	°C	125.0 min.	ASTM D 92 – 02b


YALUB®TT 33 is a premium ashless metal deactivator and corrosion inhibitor which is soluble in mineral and synthetic base stocks.

Applications: Industrial and automotive lubricants, greases and metal working fluids.

Recommended Dosage – 0.05 - 0.2%

Addition of YALUB®TT 33 in small quantities can offset the detrimental effect of sulfur in oil and grease.

Test	No Additive	0.05 % Yalub TT 33
Base Oil	VG 32* + 100 ppm sulfur**	VG 32 + 100 ppm Sulfur
ASTM D 130 100°C 3 h	4 b	1 a



*Solvent refined paraffinic Gr 1 oil. **Elemental sulfur

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED


REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai – 400058, India TEL: +91 22 62510100/FAX : +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY – UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.

Test	No Additive	0.05 % Yalub TT 33
Grease	12-OH Li Grease + 3% Yalub SIB	12-OH Li Grease + 3% Yalubb SIB
ASTM D 130 100°C 3 h	4 c	1 b

YALUB®TT 33 inhibits oxidation by chelating metal ions which catalyze oxidative degradation.



Base oil VG 32 + 0.2% of alkylated diphenylamine (Yalub BODPA)

Storage:

Store at room temperature away from moisture and sunlight.

Rev.03 DT. 01.06.2020

YALUB is a registered trademark of YASHO INDUSTRIES LIMITED and/or its respective wholly owned subsidiaries

YASHO INDUSTRIES LIMITED

REGISTERED OFFICE: Office No. 101/102, Peninsula Heights, C.D.Barfiwala Marg, Juhu lane, Andheri (West), Mumbai - 400058, India TEL: +91 22 62510100/FAX : +91 22 62510199 E-Mail: info@yashoindustries.com

FACTORY – UNIT I: Plot No. 2514/2515, Phase IV, G.I.D.C., Vapi - 396 195, Gujarat, India TEL.: +91 260 2432421 / 2426894 / 2420447

Although every care has been taken in the completion of the above information & recommendation they are offered in good faith without guarantee.